

RESILIENT FLOORING

DOCUMENT NUMBER: 09650

APPLICATION: ELEMENTARY, MIDDLE AND HIGH SCHOOL

DATE OF ISSUE:

- 03-26-14 - Revised approved floor finish
- 06-02-09 - Revised approved floor finish
- 08-25-03 - added adhesive information
- 08-01-03 - added product name
- 05-25-00 - revised number of coats required
- 12-31-98 - first issued

NOTES:

Install new VCT using epoxy based adhesive on existing concrete slabs which may not have a vapor barrier.

Vinyl Composition Tile floors shall be finished by the Contractor as follows:

Prior to Substantial Completion and occupancy by the Owner, all VCT flooring shall receive five (5) coats of **"24/7 Extended Performance Floor Finish,"** an acrylic wet-look gloss floor finish manufactured by National Chemical Laboratories, Inc. (NCL), available from American Chemical and Building Maintenance Supply, Inc., Mr. Scott A. Zirkle, (727) 822-8181. Final coat shall be buffed to a high gloss.

Application of each coat shall be in strict accordance with manufacturer's instructions, following the recommended drying time between coats and preparation for high-speed buffing. Do not apply more coats in a 24-hour period than recommended by the manufacturer.

For renovation projects where existing VCT flooring will remain, remove existing floor finish(es) and wax(es) prior to application of new floor finish, utilizing **"BARE BONES No-Rinse/No-Scrub Liquifying Stripper,"** a 55% active, low foaming, no rinse floor stripper manufactured by National Chemical Laboratories, Inc. (NCL), available from American Chemical and Building Maintenance Supply, Inc., Mr. Scott A. Zirkle, (727) 822-8181.

ATTACHMENTS:

None